

Datasheet

Description	Needle punch sport surface. Support layer of 100% structured polypropylene fibre with total impregnation, in-filled with crushed brick clay.
Destination	Outdoor and Indoor tennis courts.
Support layer	Hot rolled impermeable asphalt 0/4-0/6, non-porous concrete with cross-slope. Porous concrete. Porous asphalt. Base horizontal plane must be checked before starting installation. Deviations of 6 mm under a 3 meters rule will be tolerated. Outside this limit the base must be levelled using an appropriate and approved technical solution.
Colour	Red
Membrane Mass	1.400 g/m ² ± 10 %
Membrane Thickness	8,5 mm ± 10 %
Standard roll Width	2 m
Standard roll Length	36,20 m
Standard roll Weight	102 kg
Fire Rating	Bfl s1
Court markings	TOP CLAY [®] Line Paint, approx 60 kg per court
Infill	0/1 mm TOP CLAY [®] approved clay infill 3 to 4,5 T. per court.
Adhesive	Two-component PU glue in stripes (approx 750 g/m ²)
Playing features	ITF Category 1 «Slow». Ball bounce and playing comfort identical to traditional clay courts.
Warranty	10 years (see warranty conditions available upon request).
Maintenance	See TOP CLAY [®] Maintenance Guidelines.
Installation	See TOP CLAY [®] Installation Guidelines.
Certification	ISO 9001:2008. Certificate Number : IT 240282



We reserve the right to amend these specifications